

## M3, M4, M6 series wall mounting liquid filled dial thermometer

### Feature:

- Material of case & cover: aluminum alloy casting.  
Material of capillary tubing: stainless steel or copper steel alloy.  
Material of sensing bulb: stainless steel.
- Customer can choose the dial diameter, temperature range, capillary tubing length, number of electric contact, sensing bulb length and diameter to make a suitable thermometer.
- Additional 1 to 2 electric contacts are available. Can act as temperature controller.
- Fully mechanical, no need to worry about the power supply.

### Specification:

Series	M3	M4	M6
Dial diameter	75mm	100mm	150mm
Temperature range: (Specify when order)	-30~50°C 0~200°C	0~50°C 0~300°C	0~100°C 0~400°C
Capillary tubing length	1m/ 3m/ 5m/ 8m/ 10m		
Sensing bulb diameter	8mm/ 10mm/ 12mm/ 14mm/ 16mm		
Sensing bulb length	100mm/ 150mm/ 200mm/ 300mm/ 500mm		
Screw union	GT-S; PT1/2; GS-S; PF1/2		
Electric contact (optional)	No/ 1 point (upper or lower limit one contact)/ 2 points (upper or lower limit two contacts, upper & lower limit two contacts)		
Contact capacity	AC 200V, 0.2A; DC 200V, 0.01A		

### Common model:

Model	Description
M4-GS-S/150	Dial diameter: 100mm, Liquid filled, temperature range: 0~150°C, Capillary tubing length: 3m, Sensing bulb diameter: 12mm, Sensing bulb length: 100mm, Screw union: PT1/2



## MR10 series wall mounting liquid filled self-recording thermometer

### Feature:

- Material of case & cover: aluminum alloy casting.  
Material of capillary tubing: stainless steel or copper steel alloy.  
Material of sensing bulb: stainless steel.
- Customer can choose the dial diameter, temperature range, capillary tubing length, number of contact output, sensing bulb length and diameter to make a suitable thermometer.

### Specification:

Series	MR10 Recorder			
Dial diameter	250mm			
Temperature range: (Specify when order)	-30~50°C 0~200°C	0~50°C 0~300°C	0~100°C 0~400°C	0~150°C
Capillary tubing length	1m/ 3m/ 5m/ 8m/ 10m			
Sensing bulb diameter	8mm/ 10mm/ 12mm/ 14mm/ 16mm			
Sensing bulb length	100mm/ 150mm/ 200mm/ 300mm/ 500mm			
Screw union	GT-S; PT1/2; GS-S; PF1/2			
Quartz clock	12hrs/rev, 24hrs/rev			

### Common model:

Model	Description
MR10-GT-S/-30+50C	Sensitive liquid filled thermometer, range: -30~50°C, Capillary tubing length: 3m, Sensing bulb diameter: 12mm, Sensing bulb length: 150mm, Screw union: PT1/2

### MR10 accessories:

Model	Description	Model	Description
3002	0~150°C temperature chart paper, 24hrs, 100 sheets	3022	0~300°C temperature chart paper, 24hrs, 100 sheets
3004	0~50°C temperature chart paper, 24hrs, 100 sheets	INK-RED	Red recording ink
3016	-30~50°C temperature chart paper, 24hrs, 100 sheets	PEN-NIB	Nib



香港科學儀器社有限公司  
Che Scientific Co. (Hong Kong) Ltd.

### Hong Kong Head office:

Unit D, 18/F, Roxy Industrial Centre, 58-66 Tai Lin Pai Road, Kwai Chung, Hong Kong

TEL: (852) 2481 1323 FAX: (852) 2418 1302

E-mail: [sales@chescientific.com](mailto:sales@chescientific.com) Website: [www.chescientific.com](http://www.chescientific.com)



浙江科通儀器有限公司  
Zhejiang Fortune Scientific Co. Ltd.

TEL: (86 571) 8729 7500 FAX: (86 571) 8729 7511

E-mail: [sales@fortunescientific.com.cn](mailto:sales@fortunescientific.com.cn)

Website: [www.fortunescientific.com.cn](http://www.fortunescientific.com.cn)

### Guangzhou Branch:

TEL: (86 20) 8130 7388 FAX: (86 20) 8108 4925

E-mail: [guangzhou@fortunescientific.com.cn](mailto:guangzhou@fortunescientific.com.cn)