



“艾森”牌 针规套装 “EISEN” Pin Gauge Set

日本
Japan

EP 系列针规套装 Pin Gauge Set – [直径 0.01mm 递增]



Specifications 规格				
尺寸 Size (mm)	长度 Length (mm)	公差 Tolerance	粗糙度/圆柱度 Roundness/Cylindricity	硬度 Hardness
0.05 ... 1.49	40	±1μm	0.8μm	高于 58 HRC
1.50 ... 10.00	50			
10.01 ... 20.00		±1.5μm	1.3μm	

0.20-1.49mm 针规, 每支附独立包装筒, 筒面印有直径
1.50mm 以上 针规, 每支用激光刻印技术, 把直径印在针规身上

Set No. 套装编号	Sizes in Increments of 0.01mm 直径 0.01mm 递增	Quantity 数目
EP-00*	0.05 0.06 0.19 0.2	16
EP-0A	0.20 0.21 0.49 0.50	31
EP-0B	0.50 0.51 0.99 1.00	51
EP-1A	1.00 1.01 1.49 1.50	51
EP-1B	1.50 1.51 1.99 2.00	51
EP-2A	2.00 2.01 2.49 2.50	51
EP-2B	2.50 2.51 2.99 3.00	51
EP-3A	3.00 3.01 3.49 3.50	51
EP-3B	3.50 3.51 3.99 4.00	51
EP-4A	4.00 4.01 4.49 4.50	51
EP-4B	4.50 4.51 4.99 5.00	51
EP-5A	5.00 5.01 5.49 5.50	51
EP-5B	5.50 5.51 5.99 6.00	51
EP-6A	6.00 6.01 6.49 6.50	51
EP-6B	6.50 6.51 6.99 7.00	51
EP-7A	7.00 7.01 7.49 7.50	51
EP-7B	7.50 7.51 7.99 8.00	51
EP-8A	8.00 8.01 8.49 8.50	51
EP-8B	8.50 8.51 8.99 9.00	51
EP-9A	9.00 9.01 9.49 9.50	51
EP-9B	9.50 9.51 9.99 10.00	51

Set No. 套装编号	Sizes in Increments of 0.01mm 直径 0.01mm 递增	Quantity 数目
EP-10A	10.00 10.01 ... 10.49 10.50	51
EP-10B	10.50 10.51 ... 10.99 11.00	51
EP-11A	11.00 11.01 ... 11.49 11.50	51
EP-11B	11.50 11.51 ... 11.99 12.00	51
EP-12A	12.00 12.01 ... 12.49 12.50	51
EP-12B	12.50 12.51 ... 12.99 13.00	51
EP-13A	13.00 13.01 ... 13.49 13.50	51
EP-13B	13.50 13.51 ... 13.99 14.00	51
EP-14A	14.00 14.01 ... 14.49 14.50	51
EP-14B	14.50 14.51 ... 14.99 15.00	51
EP-15A	15.00 15.01 ... 15.49 15.50	51
EP-15B	15.50 15.51 ... 15.99 16.00	51
EP-16A	16.00 16.01 ... 16.49 16.50	51
EP-16B	16.50 16.51 ... 16.99 17.00	51
EP-17A	17.00 17.01 ... 17.49 17.50	51
EP-17B	17.50 17.51 ... 17.99 18.00	51
EP-18A	18.00 18.01 ... 18.49 18.50	51
EP-18B	18.50 18.51 ... 18.99 19.00	51
EP-19A	19.00 19.01 ... 19.49 19.50	51
EP-19B	19.50 19.51 ... 19.99 20.00	51

* EP-00 针规附把手, 长度是 5mm, 公差是 ±0.5μm
** special sizes also available 可订购特定直径针规

EM 系列针规套装 Pin Gauge Set – [直径 0.025mm 递增]



Specifications 规格				
尺寸 Size (mm)	长度 Length (mm)	公差 Tolerance	粗糙度/圆柱度 Roundness/ Cylindricity	硬度 Hardness
0.100...1.525	40	(+) size (+2 ~ +5μm)	1.3μm	高于 58 HRC
1.550...12.975	50	(-) size (-2 ~ -5μm)		
13.000...19.000		(+) size (+1 ~ +5μm)	1.6μm	

Set No. 套装编号	Sizes 尺寸	Quantity 数目
EM-00 (+) EM-00 (-)	0.100 0.110 ... 0.280 0.290 直径 0.01mm 递增	20
EM-0 (+) EM-0 (-)	0.300 0.325 ... 1.500 1.525 直径 0.025mm 递增	50
EM-1 (+) EM-1 (-)	1.550 1.575 ... 6.250 6.275 直径 0.025mm 递增	190
EM-2A (+) EM-2A (-)	6.300 6.325 ... 9.750 9.775 直径 0.025mm 递增	140
EM-2B (+) EM-2B (-)	9.800 9.825 ... 12.500 12.525 直径 0.025mm 递增	110
EM-2C (+) EM-2C (-)	12.550 12.575 ... 12.950 12.975 直径 0.025mm 递增	18
EM-3 (+) EM-3 (-)	13.000 13.100 ... 18.900 19.000 直径 0.1mm 递增	61

- 测量孔及孔间距, 槽宽, 齿轮节圆等
- 广泛用于电子行业等产品生产检测过程